

KEDEL

BRITISH RECYCLED PLASTIC PRODUCTS

Recycled Mixed
Plastic
Specification
Kedel Ultra

Specification

Description	Kedel Ultra , the stiffest of the Kedel mixed plastic blends, offers good impact resistance & bending strength. The surface has the appearance of timber with even colour. Contains polyolefins (HDPE & LDPE) & styrenes. 100% Recycled post industrial & consumer waste plastic.	
Production Process	A blended polymer, fed into molds under high temperatures and pressures.	
Finish	The surface is knot free, evenly coloured, with a textured surface.	
Properties	<ul style="list-style-type: none">◆ Maintenance free◆ Durable◆ Can be worked as wood◆ Splinter free◆ Frost proof◆ Impervious to fungi and insects◆ Does not leach toxic substances	<ul style="list-style-type: none">◆ Wear resistant◆ Will not rot◆ Environmentally friendly◆ 100% recycled and recyclable◆ Insulating◆ Acoustic sound proofing◆ Shock proof and flexible◆ Resistant to most chemicals
Performance	Properties	Example Values
All figures quoted are typical values and for guidance only	Density	0.99 g/cm ³
	Thermal expansion coefficient	0.11 mm/m/°C
	Moisture absorption (ISO 175)	<0.2 wt%
	Slip resistance in dry (BS 7976-2)	Low slip risk - 49
	Slip resistance in wet (BS 7976-2)	Low slip risk - 41
	Tensile modulus (ISO 527-2)	1445 MPa
	Tensile strength (ISO 527-2)	15 MPA
	Flexural modulus (ISO 178)	1225 MPa
	Flexural strength (ISO 178)	30 MPa
	Impact resistance un-notched (ISO 179)	14 KJ/m ²
Chemical Stability	Resistant to most common chemicals - contact us for specific info	
Typical Uses	Ideal for extreme loading - fence rails, floorboards, beams & sleepers and challenging environments where durability and strength count.	

Kedel Limited, Old Transco Depot, Oswald Street, Burnley, Lancashire, BB12 0BY
T: 01282 861325 · W: www.kedeltrade.co.uk · E: info@kedel.co.uk